

Mi-TIC 320™



Powered by the



The Mi-TIC 320 is part of the argus range of thermal imaging cameras and is the world's smallest NFPA 1801 certified high resolution thermal imager for firefighting applications. The camera provides a crystal clear image with a superb dynamic range; you can clearly view extremely high temperatures up to 1100°C (2000°F) and at the same time see very low temperature objects, which is ideal for casualty searches.

Every Mi-TIC 320 is supplied with a unique dual use desktop/in-truck charger station which securely retains and charges both the thermal imager and a spare battery. Multiple charger stations can be daisy-chained together up to a maximum of 6 units.

PERSONAL

Weighing approximately 755g (1.7lb), the Mi-TIC 320 is a small footprint thermal imager that can be easily and comfortably held in the palm of your hand. Unlike many thermal imagers, the Mi-TIC 320 design allows it to be worn in multiple ways – in the hand, inside a pocket, clipped outside a pocket, clipped to a lanyard or hung around the neck.

SIMPLE

With a thumb operated green "on/off" button and superb start-up time of 5 seconds, the Mi-TIC 320 is simple to use.

SAFE

The Mi-TIC 320 has Class I, Division 2 and Class II, Division 2 Non Incendive certifications. The use of Lithium Iron Phosphate technology ensures the Mi-TIC 320 delivers in excess of 3 hours of battery life over 2,000 plus charge cycles. The Mi-TIC rechargeable batteries are inherently safe due to the use of patented nanophosphate® technology.



CAMERA STANDARD FEATURES

The Mi-TIC 320 comes with the most advanced features available in any Thermal Imaging Camera. These include:

2.7" (69mm) LCD Display	X2 and X4 Digital Zoom
Direct Temperature Measurement (DTM)	Image Capture (1000 images)
Tri-Mode Sensitivity	Video Capture (up to 16 hours)
Customizable Start-Up Screen	"Black Box" Video Recording (up to 16 hours)
Firefighting Application Modes <ul style="list-style-type: none"> • Fire • Fire Plus • Overhaul • Size-Up 	Image Freeze
Search and Rescue Application Modes <ul style="list-style-type: none"> • White Hot • Missing Person 	User Replaceable Germanium Window (Order code: ARG_MI_RWS)
Heat Seeker	No PC Software required for image and video download – when the camera is docked, it is recognized as a removable device (like a USB memory stick)
Cold Seeker	

CAMERA STANDARD ACCESSORIES

The Mi-TIC 320 comes with the following accessories as standard:

Two argus® Mi-TIC NFPA Lithium Iron Phosphate Battery Packs (Standard) (Order code: ARG_MI_BLPN-2)	Retractable Lanyard (Order code: ARG_MI_RL)
Truck/Desktop Charger Dock Station (Order code: ARG_MI_CS)	Charger Station Mounting Bracket (Order code: ARG_MI_MB)
Charger Power Supply with US, UK, Europe, Aus and South America Plugs (Order code: ARG_MI_PSU)	USB Connection Lead for connecting dock to PC / Laptop (Order code: ARG_MI_USB)
	Pocket Clip (Order code: ARG_MI_PCLIP)
	Quick Start Guide

CAMERA OPTIONAL ACCESSORIES

"AA" Battery Pack (non-NFPA) (Order code: ARG_MI_BAA)	argus® Soft Carry Case (Order code: P7030SC)
argus® Mi-TIC 320 Black Hard Case (Order code: ARG_MI_BHC)	argus® Neck Strap (Order code: P7030NS)



CAMERA ORDER CODES

Code	Kitting	Resolution	Buttons	Frame Rate
MI-TIC-320-3	FULL KIT	320x240	3	30Hz
MI-TIC-320-3_CAM	Camera only	320x240	3	30Hz

WARRANTY

5-Year Camera Warranty
 5-Year Battery Warranty
 10-Year Focusing Lens and Sensor Warranty

ENVIRONMENTAL DATA

Thermal conditions The camera has been designed to operate:

- continuously between -20°C (-4°F) and +85°C (185°F) or
- at 150°C (300°F) for 15 minutes
- at 260°C (500°F) for 7 minutes

Sealing	IP67; will withstand short-term immersion in water
Impact	The camera will withstand a drop from a height of 2m (6.5ft) onto concrete
Storage	It is recommended that, for maximum effective operational life, the storage temperature is kept between -20°C (-4°F) and +40°C (104°F)

OPTICAL DATA

DETECTOR

Sensor type	Un-cooled Microbolometer
Sensor material	Amorphous Silicon (ASi)
Resolution	384 x 288px
Pixel size	17µm
Spectral response	7.5 – 14µm
MDTD (Full camera system sensitivity)	60mK (0.06°C) typical (Minimum Discernible Temperature Difference)
NETD (Sensor sensitivity)	<50mK (<0.05°C)
Dynamic range	-40°C to 1100°C (-40°F to 2000°F)
Refresh rate	60Hz
Direct Temperature Measurement (DTM)	-40°C to 1100°C (-40°F to 2000°F)

LENS

Lens material	Germanium Composite
Focal length	1m to infinity, optimized at 4m (3ft to infinity, optimized at 13ft)
Aperture	f/1.0
Field of view	50° horizontal, 37.5° vertical, 62° diagonal

DISPLAY

Type	High-grade, industrial, color TFT active matrix LCD
Size	69mm (2.7")
Pixel format	QVGA 320 x 240 (each pixel RGB format; total 230,400 pixels)
Video input	Sensor synchronized direct digital drive
Backlight	400cd/m ²

MECHANICAL DATA

Camera dims (H x W x D)	203mm x 96mm x 71mm (8.0" x 3.7" x 2.8")
Camera weight	580g (1.3lb) without battery 755g (1.7lb) with standard battery
Std Battery dims (H x W x D)	87mm x 76mm x 28mm (3.4" x 3.0" x 1.1")
Std Battery weight	175g (6oz)
Charger dims (H x W x D)	167mm x 112mm x 120mm (6.5" x 4.4" x 4.7")
Charger weight	600g (1.3lb)
Main camera body	Radel® R-5100 and Santoprene®
LCD window	Ultrason® E 2010 HC
LCD bumper	Santoprene®
Ge Window collar	Radel® R-5100 and Santoprene®
Lens window	Germanium (2mm thick) with durable coating

ELECTRICAL DATA

Power consumption	<3 W typical
Start-up time	5 seconds typical
Std Battery type	Lithium Iron Phosphate Rechargeable Battery
Std Battery capacity	1500 mAh, 6.6V
Std Battery life	In excess of 3 hours @ ambient temperature (22°C / 72°F)
Std Battery charge time	Less than 3 hours
Std Battery recharge cycles	Over 2000 cycles
Std Battery sealing	IP67
Std Battery charging temp.	5°C to 40°C (41°F to 104°F)
Charger input voltage	11V – 30V DC (12V and 24V vehicle systems)
Charger operating temp.	0°C to 40°C (32°F to 104°F)

COMPLIANCE DATA

Performance	NFPA 1801:2021 Standard on Thermal Imagers for the Fire Service
Safety	IEC 62368-1:2014 and related national standards UL 121201 / CSA C22.2 No. 213:2017 Class I, Div 2, Groups C, D T4; Class II, Div 2 Groups F, G T4
Emissions RFI/EMC	EN 55032:2015, Class A EN 54098:2010 FCC CFR 47 subpart 15b, ICES 003:2017 AUS/NZ 4251.1
Immunity	EN 55103-2:2009
Vibration/Shock	BS EN 60721-3-2 Class 2M3
RoHS	All parts of the system are compliant with EU directive 2011/65/EC

Copyright © 2021 Avon Protection. All rights reserved.
 GR03145-04

