

# Mi-TIC S™



Powered by the



## INTRODUCTION

The Mi-TIC S is part of the argus range of thermal imaging cameras and the world's smallest thermal imager to feature a large format, high resolution display for advanced firefighting applications. The camera provides a crystal clear image with a superb dynamic range; you can clearly view extremely high temperatures up to 1100°C (2000°F) and at the same time see very low temperature objects, which is ideal for casualty searches.

Every Mi-TIC S is supplied with a unique dual use desktop/in-truck charger station which securely retains and charges both the thermal imager and a spare battery. Multiple charger stations can be daisy-chained together up to a maximum of 6 units.

## PERSONAL

Weighing approximately 870g (1.9lb), the Mi-TIC S is a small footprint thermal imager that can be easily and comfortably held in the palm of your hand. Unlike many thermal imagers, the Mi-TIC S design allows it to be worn in multiple ways – in the hand, inside a pocket, clipped outside a pocket, clipped to a lanyard or hung around the neck.

## SIMPLE

With a thumb operated green "on/off" button and superb start-up time of 5 seconds, the Mi-TIC S is simple to use.

## SAFE

The argus Mi-TIC S has Class I, Division 2 and Class II, Division 2 Non Incendive certifications. The use of Lithium Iron Phosphate technology ensures the Mi-TIC S delivers in excess of 3 hours of battery life over 2,000 plus charge cycles. The Mi-TIC rechargeable batteries are inherently safe due to the use of patented nanophosphate® technology.



## CAMERA STANDARD FEATURES

The Mi-TIC S comes with the most advanced features available in any Thermal Imaging Camera. These include:

|                                      |  |
|--------------------------------------|--|
| 3.5" (90mm) LCD Display              | X2 and X4 Digital Zoom   |
| Direct Temperature Measurement (DTM) | Laser Pointer  |
| Tri-Mode Sensitivity                 | Electronic Compass   |
| Customizable Start-Up Screen         | Image Capture (1000 images)  |
| Firefighting Applications Modes:     | Video Capture (up to 16 hours)   |
| • Fire                               | "Black Box" Video Recording (up to 16 hours)   |
| • Fire Plus                          | Image Freeze   |
| • Overhaul                           | User Replaceable Germanium Window (Order code: ARG_MI_RWS)   |
| • Size-Up                            | No PC Software required for image and video download – when the camera is docked, it is recognized as a removable device (like a USB memory stick) |
| Search and Rescue Application Modes: |  |
| • White Hot                          |  |
| • Missing Person                     |  |
| Heat Seeker                          |  |
| Cold Seeker                          |  |

## CAMERA STANDARD ACCESSORIES

The Mi-TIC S comes with the following accessories as standard:

|  |   |
|--|---|
| Two argus® Mi-TIC Lithium Iron Phosphate Battery Packs (Standard)<br>(Order code: ARG_MI_BLPNS-2; NSN: 6140-99-271-4958) | Retractable Lanyard<br>(Order code: ARG_MI_RL)  |
| Desktop/Vehicle Charger Station<br>(Order code: ARG_MI_CS; NSN: 6130-99-388-7164)  | Charger Station Mounting Bracket<br>(Order code: ARG_MI_MB; NSN: 5340-99-705-4328)                        |
| Charger Power Supply with US, UK, Europe, Aus and South America Plugs<br>(Order code: ARG_MI_PSU; NSN: 6130-99-513-9799) | USB Connection Lead for connecting dock to PC / Laptop<br>(Order code: ARG_MI_USB; NSN: 5995-99-938-6020) |
|  | Pocket Clip<br>(Order code: ARG_MI_PCLIP_S)   |
|  | Quick Start Guide   |

## CAMERA OPTIONAL ACCESSORIES

|   |   |
|---|---|
| "AA" Battery Pack (non-NFPA)<br>(Order code: ARG_MI_BAA)  | argus® Soft Carry Case<br>Order code: (P7030SC) |
| argus® Mi-TIC Black Hard Case<br>(Order code: ARG_MI_BHC) | argus® Neck Strap<br>Order code: (P7030NS)      |



## CAMERA ORDER CODES

| Code           | NSN              | Kitting     | Resolution | Frame Rate |
|----------------|------------------|-------------|------------|------------|
| MI-TIC-S-3     | 5855-99-258-4363 | FULL KIT    | 320x240    | 30Hz       |
| MI-TIC-S-3_CAM | N/A              | Camera only | 320x240    | 30Hz       |

## WARRANTY

5-Year Camera Warranty  
 5-Year Battery Warranty  
 10-Year Focusing Lens and Sensor Warranty

## ENVIRONMENTAL DATA

|                           |  |
|---------------------------|--|
| <b>Thermal conditions</b> | The camera has been designed to operate: <ul style="list-style-type: none"> <li>• continuously between -20°C (-4°F) and +85°C (185°F) or</li> <li>• at 150°C (300°F) for 15 minutes</li> <li>• at 260°C (500°F) for 5 minutes</li> </ul> |
| <b>Sealing</b>            | IP67; will withstand immersion in water  |
| <b>Impact</b>             | The camera will withstand a drop from a height of 2m (6.5ft) onto concrete   |
| <b>Storage</b>            | It is recommended that, for maximum effective operational life, the storage temperature is kept between -20°C (-4°F) and +40°C (104°F)   |

## OPTICAL DATA

### DETECTOR

|  |  |
|--|--|
| <b>Sensor type</b>                           | Un-cooled Microbolometer   |
| <b>Sensor material</b>                       | Amorphous Silicon (ASi)  |
| <b>Resolution</b>                            | 384x288px  |
| <b>Pixel size</b>                            | 17µm   |
| <b>Spectral response</b>                     | 7.5 – 14µm   |
| <b>MDTD (Full camera system sensitivity)</b> | 50mK (0.05°C) typical (Minimum Discernible Temperature Difference) |
| <b>NETD (Sensor sensitivity)</b>             | <50mK (<0.05°C)  |
| <b>Dynamic range</b>                         | -40°C to 1100°C (-40°F to 2000°F)                                  |
| <b>Refresh rate</b>                          | 60Hz   |
| <b>Direct Temperature Measurement (DTM)</b>  | -40°C to 1100°C (-40°F to 2000°F)                                  |

### LENS

|                      |  |
|----------------------|--|
| <b>Lens material</b> | Germanium Composite  |
| <b>Focal length</b>  | 1m to infinity, optimized at 4m (3ft to infinity, optimized at 13ft) |
| <b>Aperture</b>      | f/1.0  |
| <b>Field of view</b> | 50° horizontal, 37.5° vertical, 62° diagonal                         |

### DISPLAY

|                     |  |
|---------------------|--|
| <b>Type</b>         | High-grade, industrial, color TFT active matrix LCD        |
| <b>Size</b>         | 90mm (3.5")  |
| <b>Pixel format</b> | QVGA 320x240 (each pixel RGB format; total 230,400 pixels) |
| <b>Video input</b>  | Sensor synchronized direct digital drive                   |
| <b>Backlight</b>    | 350 cd/m²  |

## MECHANICAL DATA

|                                     |  |
|-------------------------------------|--|
| <b>Camera dims (H x W x D)</b>      | 216mm x 110mm x 82mm with standard battery (8.5" x 4.3" x 3.2")    |
| <b>Camera weight</b>                | 695g (1.5lb) without battery<br>870g (1.9lb) with standard battery |
| <b>Std Battery dims (H x W x D)</b> | 87mm x 76mm x 28mm (3.4" x 3.0" x 1.1")                            |
| <b>Std Battery weight</b>           | 175g (6oz)   |
| <b>Charger dims (H x W x D)</b>     | 167mm x 112mm x 120mm (6.5" x 4.4" x 4.7")                         |
| <b>Charger weight</b>               | 600g (1.3lb)   |
| <b>Main camera body</b>             | Radel® R-5100 and Santoprene®                                      |
| <b>LCD window</b>                   | Ultrason® E 2010 HC  |
| <b>LCD bumper</b>                   | Santoprene®  |
| <b>Ge Window collar</b>             | Radel® R-5100 and Santoprene®                                      |
| <b>Lens window</b>                  | Germanium (2mm thick) with durable coating                         |

## ELECTRICAL DATA

|                                    |  |
|------------------------------------|--|
| <b>Power consumption</b>           | <3 W typical   |
| <b>Start-up time</b>               | 5 seconds typical  |
| <b>Std Battery type</b>            | Lithium Iron Phosphate Rechargeable Battery              |
| <b>Std Battery capacity</b>        | 1500mAh, 6.6V  |
| <b>Std Battery life</b>            | In excess of 3 hours @ ambient temperature (22°C / 72°F) |
| <b>Std Battery charge time</b>     | Less than 3 hours  |
| <b>Std Battery recharge cycles</b> | Over 2000 cycles   |
| <b>Std Battery charging temp.</b>  | 5°C to 40°C (41°F to 104°F)                              |
| <b>Charger input voltage</b>       | 11V – 30V DC (12V and 24V vehicle systems)               |
| <b>Charger mains adapter</b>       | 100V - 240V (50Hz - 60Hz)                                |
| <b>Charger operating temp.</b>     | 0°C to 40°C (32°F to 104°F)                              |

## COMPLIANCE DATA

|                          |   |
|--------------------------|---|
| <b>Performance</b>       | NFPA 1801:2021 Standard on Thermal Imagers for the Fire Service   |
| <b>Safety</b>            | IEC 62368-1:2014 and related national standards<br>UL 121201 9th Ed. / CSA C22.2 No. 213:2017 Class I, Div 2, Groups C, D T4; Class II, Div 2, Groups F, G T4<br>CAN/CSA C22.2 No. 61010-1-12<br>UL 61010-1 3rd Ed. |
| <b>Standard Battery</b>  | IEC 62133-2:2017<br>UN/DOT 38.3   |
| <b>Emissions RFI/EMC</b> | EN 55032:2015, Class A<br>EN 54098:2010<br>FCC CFR 47 subpart 15b, ICES 003:2017<br>AUS/NZ 4251.1   |
| <b>Immunity</b>          | EN 55103-2:2009   |
| <b>RoHS</b>              | All parts of the system are compliant with EU directive 2011/65/EC  |
| <b>Laser</b>             | IEC/EN 60825:2014 & 21 CFR 1040.10 & 1040.11 except for deviations pursuant of Laser Notice No. 50, dated June 24, 2007   |
| <b>Rollover</b>          | Meets requirements of NFPA 1901:2016 Standard for Automotive Fire Apparatus   |

