FMI2 ТМ

TRIED AND TRUSTED WORLDWIDE



AIR PURIFYING RESPIRATOR







The legendary FM12[™] mask is the most widely used respirator across the world by military and law enforcement organisations. Providing high levels of respiratory protection against CBRN agents and Toxic Industrial Materials, the FM12[™] has CE Marking approval.

The FM12[™] is the standard issue respirator in a variety of countries, including the Netherlands, Norway Ireland and Denmark. In today's changing world, the increasing threat of terrorist attacks has lead to law enforcement agencies requiring CBRN respiratory protection. Due to its pedigree, ease of use and high protection levels, the FM12[™] now finds itself as an essential part of the armoury of a variety of agencies including the British Police force, Singapore Police, and Chicago Police Department.

FMI2[®]

FEATURES

EYEPIECES

- Low profile polycarbonate eyepieces
- Optimal light transmission and optical clarity
- Impact and scratch resistant
- Sight correction available

FILTRATION

All filter connections are via the 40mm standard NATO thread.

CE approved (technical file) for the widest range of potential chemical, biological and radiological agents CBRNF12CE

COMMUNICATIONS

Speech horn allows clear direct communication through exhale valve.

CERTIFICATION

■ Type-examination approval: PPE Regulation 2016/425/EU - Module B: Certificate CE 684844.

TRIED AND TRUSTED WORLDWIDE

FEATURES



USER COMFORT

- 3 sizes ensures best fit for all
- 6 buckle fit allows excellent seal, 4 buckles are pre-adjusted when fitted with 2 being adjustable to allow quick donning and doffing.
- Compatible with weapon sights and other optical devices.
- Flexible contoured face seal ensures compatibility with a variety of helmets and CBRN suits.
- Side mounted filter mount minimises interference left or right mounting available for tactical specialists.
- High flow fail safe drinking device enables connection to a canteen or bladder type system.
- Internal mask design provides ideal airflow management minimising heat build-up and ensuring low re-breathed carbon dioxide.

FMI2 Filter Specifications / Applications

Filter	Classification	Application	Weight (approx)
CBRNF12CE	TECHNICAL FILE PPE Directive 2016/425/EU 1. EN14387:04 Toxic Industrial Materials A1 B2 E1 K1 P3D 2. CBRN (meets NIOSH Cap1) 3. NBC agents (nerve, blood, choking)	Classification for industrial and CBRN applications. All particulate hazards including dust, mist, fume, bacteria and virus plus all NIOSH specified CBRN test agents. NBC agents including nerve, blood, choking and blister agents.	340g

FMI2 Filter Specifications / Applications

Parameter	Requirement	FM12 performance
NIOSH Smartman RLAT system agent performance - HD	Permeation less than 3 mg-min/m ³	Permeation less than 0.1 mg-min/m ³
NIOSH Smartman RLAT system agent performance - GB	Permeation less than 1.05 mg-min/m ³	Permeation less than 0.07 mg-min/m ³
Laboratory protection factor performance (sodium chloride)	Greater than 2,000	Greater than 10,000
Re-breathed CO ₂	Less than 1%	0.76%
Inhalation resistance at 85 l/min (with CBRNF12 canister)	Less than 65 mm WG	Less than 55 mm WG
Weight of canister	Less than 500 gram	Approx 340 gram
Total weight mask and canister	N/A	Approx 790 gram
Field of view (NIOSH Visual Field Score)	Greater than 90	97

The Americas

t: +1 888 286 6440 e: customerservice@avon-protection.com

Europe, Middle East, Asia, Africa & Australasia t: +44 (0) 1225 896705

e: protection@avon-protection.com

GR13243-03

Avon Protection and Avon Protection Systems are trading names of Avon Rubber p.l.c. (registered in England with number 32960). The Avon name and logo is the registered trademark of Avon Rubber p.l.c. © Avon Rubber p.l.c 2011.





www.avon-protection.com